SIEMENS

Data sheet 6AV7881-2AB00-8EA0

No longer available SIMATIC IPC277D (Nanopanel PC) 9" Touch TFT, 2x 10/100/1000 Mbps Ethernet RJ45; 3x USB V2.0 (high current); 1x serial (COM 1); CompactFlash slot; 24 V DC power supply ATOM E640 (1.0 GHz), 1 GB RAM; Retentivity standard front 80 GB Solid-State-Drive SATA Windows 7 SP1, MUI (SSD) without SIMATIC software

Display	
Design of display	9" TFT touch
Screen diagonal	9 in
Resolution (pixels)	
● Horizontal image resolution	800 pixel
● Vertical image resolution	480 pixel
Backlighting	
● MTBF backlighting (at 25 °C)	80 000 h
Control elements	
Input device	
● Mouse, at front	No
Keyboard fonts	
● Function keys	No
● alphanumeric keyboard	No
Touch operation	
● Design as touch screen	Yes
Installation type/mounting	
central design	Yes
distributed design	No
Mounting in portrait format possible	Yes
Power loss	
In full configuration	31.2 W
Accessories	
Accessory components	Touch protective foil
Dimensions	
Width of the housing front	274 mm
Height of housing front	190 mm
Mounting cutout, width	251 mm
Mounting cutout, height	166 mm
Overall depth	71 mm
Weights	
Weight, approx.	1.9 kg
Approvals / Certificates	

General Product Approval | **Marine / Shipping**

EG-Konf. | UK CA | Manufacturer Declaration | KC | RCM | ABS

Marine / Shipping | **Dangerous goods** | **Environment**

DNV | CCS (China Classification Society) | KR | Dangerous goods information | Environmental Confirmations

last modified: 12/15/2021

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens