SIEMENS

## Data sheet 6AV7885-2AA20-1DA2

***no longer available*** SIMATIC HMI IPC 577C PCI slot, 4 USB (back)+1 USB (front), Ethernet (10/100/1000), 15" touch display ; Celeron M 1.2 GHz, PROFINET (IE); 2x 1 Gbit 2 GB -RAM, DDR3; 2nd mass storage: Not equipped 1st mass storage (Operating system optional): 320 GB HDD SATA WinXP Prof. pre-installed (only possible with HD or SSD) without expansion (software) 110/230 V AC power supply unit with NAMUR, Power supply cable Europe

| | |
|---|---|
| **General information** | |
| Product type designation | IPC577C |
| **Display** | |
| Design of display | 15" TFT touch |
| Screen diagonal | 15 in |
| Resolution (pixels) | |
| ● Horizontal image resolution | 1 024 pixel |
| ● Vertical image resolution | 768 pixel |
| Backlighting | |
| ● MTBF backlighting (at 25 °C) | 50 000 h |
| **Control elements** | |
| Input device | |
| ● Mouse, at front | No |
| Keyboard fonts | |
| ● Function keys | No |
| — Number of function keys | 0 |
| ● alphanumeric keyboard | No |
| Touch operation | |
| ● Design as touch screen | Yes |
| **Installation type/mounting** | |
| central design | Yes |
| distributed design | No |
| maximum permissible installation angle +/- | 45° |
| **Supply voltage** | |
| Type of supply voltage | 110/230 V AC or 24 V DC |
| **Power loss** | |
| In full configuration | 24 V DC: max. 80 W (incl. USB interfaces) |
| **Processor** | |
| Processor type | Intel Celeron M 1.2 GHz, Intel Core2Solo 1.2 GHz, Intel Core2Duo 1.86 GHz |
| **Drives** | |
| Optical drives | Optional: DVD±R±RW combi drive; on rear, can be operated from side |
| Hard disk | 3.5" SATA hard disk ≥ 80 GB, vibration-resistant mounting |
| **Memory** | |
| Type of memory | DDR3-SDRAM |
| Main memory | 512 MB |
| Capacity of main memory, max. | 4 096 Mbyte; At least 3.2 GB can be used |
| **Data areas and their retentivity** | |
| Retentive data area (incl. timers, counters, flags), max. | 2 048 kbyte; 128 KB can be stored in the buffer time |
| **Hardware configuration** | |
| Slots | |
| ● free slots | 1x CF card slot, externally accessible, 1x PCI slot in device interior, 1x SSD slot |
| ● Number of PCI slots | 1 |
| ● Number of compact flash slots | 1 |
| **Interfaces** | |
| PROFIBUS/MPI | 1x CP5611 comptable |
| USB port | 1x on front, 4x on reverse, USB 2.0 (3x 500 mA) |
| Connection for keyboard/mouse | USB / USB |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| parallel interface | 0 |
| Multimedia | |
| ● Audio In/Out | No |
| ● Microphone In | No |
| Video interfaces | |
| ● Graphics interface | DVI-I: VGA / DVI combined |
| Industrial Ethernet | |
| ● Industrial Ethernet interface | PROFIBUS version, onboard 2 x: PROFINET version, onboard 1 x: 10/100/1000 Mbit/s, RJ45, no plug-in card necessary. |
| — 100 Mbps | Yes |
| — 1000 Mbps | Yes |
| **Integrated Functions** | |
| Monitoring functions | |
| ● Temperature monitoring | Yes |
| ● Watchdog | Yes |
| **Degree and class of protection** | |
| IP (at the front) | IP65 |
| **Standards, approvals, certificates** | |
| CE mark | Yes |
| EMC | CE, EN 61000-6-4; CISPR 22:2004 Class A; FCC Class A |
| Marine approval | |
| ● Germanischer Lloyd (GL) | No |
| ● American Bureau of Shipping (ABS) | No |
| ● Bureau Veritas (BV) | No |
| ● Det Norske Veritas (DNV) | No |
| ● Lloyds Register of Shipping (LRS) | No |
| ● Polski Rejestr Statkow (PRS) | No |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | 0 °C |
| ● max. | 50 °C |
| Relative humidity | |
| ● Relative humidity | Tested according to IEC 60068-2-78, IEC 60068-2-30: Operation: 5% to 85% at 30 °C (no condensation) Storage: 5% to 95% at 25 °C (no condensation) |
| Vibrations | |
| ● Vibration resistance during operation acc. to IEC 60068-2-6 | Mech. environmental conditions tested in acc. with IEC 60068-2-6 Vibration: in operation with CompactFlash Card and SSD: 10 Hz to 58 Hz: 0.075 mm, 58 Hz to 500 Hz: 9.8 m/s²; in operation with HDD: 10 Hz to 58 Hz: 0.0375 mm, 58 Hz to 500 Hz: 4.9 m/s² |
| **Operating systems** | |
| pre-installed operating system | Windows XP Embedded and Win XP Prof. |
| Additional info on operating system | WIN XPe: GER/ENG WIN XP Prof: MUI Language: GER, ENG, IT, FR, SP, KOR, CHN (traditional), CHN (simplified), JPN |
| without operating system | Yes |
| pre-installed operating system | |
| ● Windows XP Professional | Yes; Only with SSD or HDD |
| **Accessories** | |
| Accessory components | Touch protective foil |
| **Dimensions** | |
| Width of the housing front | 483 mm |
| Height of housing front | 310 mm |
| Mounting cutout, width | 450 mm |
| Mounting cutout, height | 290 mm |
| Overall depth | 120 mm |
| ● additional mounting depth (optical drive) | 23 mm |
| **Weights** | |
| Weight, approx. | 9 kg |
| **Approvals / Certificates** | |

| General Product Approval | Test Certificates | other | Environment |
|---|---|---|---|


Subject to change without notice
© Copyright Siemens

EG-Konf.

Type Test Certificates/Test Report | Confirmation | Environmental Confirmations

**last modified:** 10/16/2020


Subject to change without notice
© Copyright Siemens