



Figure similar

*** spare part *** SIMATIC S7-200 CN, Digital I/O EM 223, only for S7-22X CPU, 8 DI 24 V DC, sink/source, 8 DO 24 V DC; 0.75 A/channel source this S7-200 CN product only has CE approval

Power loss			
Power loss, typ.	3 W		
Digital inputs			
Number of digital inputs	8		
Input voltage			
• Type of input voltage	DC		
• Rated value (DC)	24 V		
Input current			
• for signal "1", typ.	4 mA		
Digital outputs			
Number of digital outputs	8		
Short-circuit protection	No		
Limitation of inductive shutdown voltage to	L+ (-48 V)		
Output current			
• for signal "1" rated value	750 mA		
Dimensions			
Width	71.2 mm		
Height	80 mm		
Depth	62 mm		
Classifications			
		Version	Classification
	eClass	14	27-24-22-04
	eClass	12	27-24-22-04
	eClass	9.1	27-24-22-04
	eClass	9	27-24-22-04
	eClass	8	27-24-22-04
	eClass	7.1	27-24-22-04
	eClass	6	27-24-22-04
	ETIM	9	EC001419
	ETIM	8	EC001419
	ETIM	7	EC001419
	IDEA	4	3566
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Ap- proval	Marine / Shipping		



[CCS \(China Classification Society\)](#)

last modified:

8/22/2024 