SIEMENS

Data sheet 6GT2821-1AC32

product type designation	**RF210R reader IO-Link**
	SIMATIC RF200 reader RF210R IO-Link IO-Link interface IP67, -25 to +70 °C; M18x 83 mm; with integrated antenna 8 Byte IO; 38.4 Kbit/s.



suitability for operation	ISO 15693 transponder (MDS Dxxx), for connecting to IO-Link Master V1.0
radio frequencies	
operating frequency / rated value	13.56 MHz
range / maximum	20 mm; Range is dependent on transponder type: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	ISO 15693, ISO 18000-3
transfer rate / with radio transmission / maximum	26.5 kbit/s
product feature / multitag-capable	No
electrical data	
transfer rate / at the point-to-point connection / serial / maximum	38.4 kbit/s
transmission time / for user data	
● for write access / per byte / typical	40 ms
● for read access / per byte / typical	40 ms
data volume / of the address range of the inputs / total	8 byte
data volume / of the address range of the outputs / total	8 byte
interfaces	
standard for interfaces / for communication	IO-Link V1.0
type of electrical connection	M12, 4-pin
mechanical data	
material	Brass, nickel-plated / PBT
color	silver/pastel turquoise
tightening torque / of the screw for securing the equipment / maximum	20 N·m
mounting distance / relating to metal surfaces / recommended / minimum	0 mm
supply voltage, current consumption, power loss	
supply voltage / at DC	
● rated value	24 V
●	20.4 ... 28.8 V
consumed current / at DC	
● at 24 V / typical	0.05 A
ambient conditions	
ambient temperature	
● during operation	-20 ... +70 °C
● during storage	-25 ... +80 °C
● during transport	-25 ... +80 °C
protection class IP	IP67
shock resistance	EN 60721-3-7 Class 7 M2
shock acceleration	500 m/s²
vibrational acceleration	200 m/s²

Subject to change without notice
© Copyright Siemens

design, dimensions and weights	
height	83 mm
diameter	18 mm
net weight	0.065 kg
fastening method	2 nuts M18 x 1 (included in scope of supply)
wire length	
● between master and IO-Link device / maximum	20 m
product features, product functions, product components / general	
display version	3-color LED
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	Radio according to R&TTE guidelines EN300 330 and EN 301489, FCC, cULus
certificate of suitability	
● IECEx	No
MTBF	505 a
reference code	
● according to IEC 81346-2:2019	BYB
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	43.51 kg
● during manufacturing	10.7 kg
● during operation	32.51 kg
● after end of life	0.3 kg
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to web page: RFID country approval	https://www.siemens.com/rfid-approvals
● to web page: identification and localization systems	https://www.siemens.com/ident
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval






Declaration of Conformity




EMV	Radio Equipment Type Approval Certificate	Environment

Subject to change without notice
© Copyright Siemens

KC	Miscellaneous	Miscellaneous	Miscellaneous	Confirmation

last modified: 3/25/2025

Subject to change without notice
© Copyright Siemens