Completely pre-assembled Signal Towers / KOMPAKT 37

# K37cl sr plug EM Pulse tone 12VAC/DC GN/



| | |
|---|---|
| **Part No.:** | **699.410.74** |
| **Series:** | **Kompakt 37** |

| MECHANICAL DATA | |
|---|---|
| Height | 175 mm |
| Diameter | 38 mm |
| Materials | PC |
| Dome colour | Clear |
| Housing colour | Silver |
| Protection category | IP65 |
| Connection | M12 plug 5-pole |
| Cable entry | Membrane grommet |
| Cable entry minimum | d = 1 mm |
| Cable entry maximum | d = 9 mm |
| Cable length | 150 mm |
| Tension relief | Pull-out protection |
| Type of fixing | Built-in mounting |
| Working temperature minimum | -20°C |
| Working temperature maximum | +50°C |
| Weight with packaging | 136 g |
| Product weight | 94 g |

| ELECTRICAL DATA | |
|---|---|
| Operating voltage | 12V |
| Operating voltage type | AC/DC |
| Operating voltage frequency | 50Hz |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 12 VDC |
| Rated operational current | 295 mA |
| Rated inrush current | 500 mA |
| Protection class | Protection class 2 |
| Pollution degree | 3<br>In the connection area: 2 |

| OPTICAL DATA | |
|---|---|
| Light source | LED |
| Light colour | Green<br>Red<br>Yellow |
| Optical signal image | Permanent |
| Service life optical | 50,000 h maximum |

| ACOUSTIC DATA | |
|---|---|
| Volume (max) at 1m distance | 80,0 dB (A) |

! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

Completely pre-assembled Signal Towers / KOMPAKT 37

# K37cl sr plug EM Pulse tone 12VAC/DC GN/

| | |
|---|---|
| Acoustic signal image | Pulse tone |
| Number of tones | 1 tone |
| Audio frequency | 2900 Hz |
| Acoustic service life | 5,000 h maximum |

| **APPROVAL DATA** | |
|---|---|
| Conforms with CE | Yes |
| Conforms with RoHS directive | Yes |
| WEEE | Yes |
| Conforms with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with UL | cULus |
| UL Type Rating | Type 12<br>Type 4X |
| Conforms with FCC | No |
| Conforms with ISED | No |
| EAC certificate available | No |
| Conforms with UKCA (Importer) | Yes (WERMA (UK) Ltd.) |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |
| Conforms with VdS | No |

! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

Completely pre-assembled Signal Towers / KOMPAKT 37

# K37cl sr plug EM Pulse tone 12VAC/DC GN/

## DRAWING




! For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.